



<b>CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR</b>	Tufted 1/10" Frisé Tufté 1/10" Frisé Getuftet 1/10" Frisé Getuft 1/10" Frisé	<b>PILE DENSITY DENSITE DU VELOURS POLROHDICHTÉ POOLDICHTHEID</b>	Ca. 0,309 g/cm <sup>3</sup>	<b>IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNGMAß GELUIDSISOLATIE</b>	ISO 140-8 27 dB
<b>PILE MATERIAL COUCHE D'USURE POLMATERIAL POOLMATERIAAL</b>	Polyamide 6.6, HS Frisé	<b>TUFT DENSITY NOMBRE DE TOUFFES NOPPENZAHL AANTAL PUNTEN</b>	Ca. 260.800 /m <sup>2</sup>	<b>SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE</b>	ISO 354 0,15
<b>PRIMARY BACKING DOSSIER PRIMAIRE TRÄGER-/GRUNDMATERIAL DRAAGDOEK</b>	Polyester nonwoven	<b>CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE</b>	EN 1307 23/33- LC3	<b>PERMANENT ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH</b>	ISO 6356 < 2,0 kV
<b>SECONDARY BACKING DOSSIER SECONDAIRE RÜCKENAUSSTATTUNG RUGAFWERKING</b>	Actionbac	<b>CASTOR CHAIR SUITABILITY EMPLOI CHAISE A ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID</b>	EN 985 Intensive use	<b>TRANSVERSAL RESISTANCE RESISTANCE TRANSVERSALE DURCHGANGSWIDERSTAND DOORGANGSWEERSTAND</b>	ISO 10965 < 10 <sup>11</sup> Ohm
<b>TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT</b>	Ca. 2300 g/m <sup>2</sup>	<b>FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG</b>	EN 13501-1 Bfl-s1	<b>SIZE DIMENSION ABMESSUNG AFMETINGEN</b>	2m wide
<b>PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT</b>	Ca. 1200 g/m <sup>2</sup>	<b>FASTNESS TO LIGHT SOLIDITE A LA LUMIERE LICHTECHTHEIT LICHTECHTHEID</b>	ISO 105-B02 > 5	<b>NUMBER OF COLORS NOMBRE DE COLORIS ANZAHL DER FARBEN AANTAL KLEUREN</b>	Unlimited
<b>PILE ABOVE BACKING POIDS DE VELOURS UTILE POLNUTZSCHICHTGEWICHT NUTTIG POOLGEWICHT</b>	Ca. 916 g/m <sup>2</sup>	<b>RUBBING FASTNESS SOLIDITE AU FROTTLEMENT REIBECHTHEIT WRIJFECHTHEID</b>	Oekotex <sup>®</sup> 100 5		
<b>TOTAL HEIGHT EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE</b>	Ca. 9 mm	<b>COLOUR FASTNESS TO WATER SOLIDITE A L'EAU WASSERECHEIT WATERECHEID</b>	Oekotex <sup>®</sup> 100 Change in colour: 4-5 Staining: 4		
<b>PILE HEIGHT EPAISSEUR DU VELOURS POLDICKE POOLHOOGTE</b>	Ca. 7 mm	<b>THERMAL RESISTANCE RESISTANCE THERMIQUE WARMEDURCHLABWIDERSTAND WARMTEDOORLAATWEERSTAND</b>	ISO 8302 0,074 m <sup>2</sup> K/W		

